

VOYAGER/8 QP

The Voyager 8 Quad Power (QP) is an eight slot chassis with four separate power elements for multi-enclave applications.

It is based on the award winning Voyager 8 carbon fibre case and chassis. The chassis power system can be divided into four quadrants so that four separately powered enclaves can exist within the Voyager 8 QP chassis and case.



KEY FEATURES

- Voyager 8 form factor case and chassis
- Supports upto four enclaves
- AC or DC power with 250 W available per enclave
- Each enclave is powered via separate AC and DC power inlets to provide electrical isolation between enclaves
- Any power quadrant is field replaceable (FRU) and can be removed from the chassis without impacting the live functionality of other quadrants for ease of maintenance
- Battery back-up option available using the proven Voyager 1 or Voyager 1+ UPS if required



RUGGED



SECURE



VEHICLE POWERED

EMEA:

Klas,
4th Floor, One Kilmainham Square,
Inchicore Road, Kilmainham,
Dublin 8, Ireland
DO8 ET1W.
Tel: +353 1 6624270

US

Klas Government
450 Springpark Place,
Suite 1200,
Herndon, VA 20170
Tel: +1 571-375-2500

www.klasgroup.com

KLAS

VOYAGER/8 QP

Specifications



PHYSICAL SPECIFICATIONS

- 22.5" W x 14.2" D x 10.1" H (571 x 360 x 257 mm) with removable 19" rack mountable chassis
- 32.3 lb / 14.6 kg

CONSTRUCTION

- Aerospace-grade, multidirectional carbon fiber transit case
- Milled aluminum hardware
- Neoprene O-ring watertight seal
- Manual pressure equalization valve
- Aluminum sheet metal
- Milled aluminum latches
- Fan cooled (each power quadrant has an internal fan)
- 19" rack mountable

HANDLES

- Retractable extension handle
- Grab handles on top and bottom of case

OPERATING TEMPERATURE RANGE

- -40°C to 50°C

STORAGE TEMPERATURE RANGE

- -40°C to 85°C

ELECTRICAL INPUT SPECIFICATION

- 90 - 264 VAC via four separate C14 IEC inlets
- 18 to 40V (25 Amps max) via PT02E-12-8P MIL-STD-1275E
- M6 Earth stud

ELECTRICAL OUTPUT SPECIFICATIONS

- Each power quadrant can deliver up to 250 W
- Each slot interface can deliver 12V at 120 W
- Each quadrant can deliver 52V at 60 W for PoE

STANDARDS

- IEC 60529 IP67
- Built to MIL-STD-461
- Built to MIL-STD-810
- Built to MIL-STD-1275E
- CE
- FCC CFR 47 Part 15 Subpart B Class A
- RoHS Directive
- IEC 61000-4-2 & IEC 61000-4-5 Rugged



Voyager 8 QP Rear

EMEA:

Klas,
4th Floor, One Kilmainham Square,
Inchicore Road, Kilmainham,
Dublin 8, Ireland
D08 ETIW.
Tel: +353 1 6624270

US

Klas Government
450 Springpark Place,
Suite 1200,
Herndon, VA 20170
Tel: +1 571-375-2500

www.klasgroup.com

KLAS