

VOYAGER/SW10GG

VoyagerSW10GG brings Cisco's ESS9300 high-bandwidth switch to the Voyager ecosystem.

With the benefits of Cisco IOS-XE, VoyagerSW10GG makes it easier to network high-bandwidth datacenter and cloud applications in remote and austere locations.



KEY FEATURES

- High-bandwidth (10x 10GbE) to process large data volumes
- Cisco IOS XE switching and security for highly secure voice, video, and data communications
- Traffic prioritization of mission-critical data flows
- Voyager Ignition Key (VIK) support for easy deployment and rapid declassification
- Built TrueTactical™ for reliable operation in extreme temperatures, shock, and vibration
- Scalable with simplicity and unified management using Cisco DNA Center



SECURE



PORTABLE



RUGGED

EMEA:
Klas,
4th Floor, One Kilmainham Square,
Inchicore Road, Kilmainham,
Dublin 8, Ireland
D08 ETW.
Tel: +353 1 6624270

US
Klas Government
450 Springpark Place,
Suite 1200,
Herndon, VA 20170
Tel: +1 571-375-2500

www.klasgroup.com

KLAS

VOYAGER/SW10GG

Specifications



PHYSICAL SPECIFICATIONS

- 7.4" W x 6.3" L x 2" H (188 x 160 x 52 mm)
- 2.9 lb / 1.3 kg

ELECTRICAL SPECIFICATIONS

- 9-36 VDC input
- Power consumption: 35W typical

PORTS

- 10 x 10 Gbps SFP+ ports
- 1 x 1 Gbps management port
- 1 x Voyager Ignition Key (VIK) port
- 1 x SD card slot
- 1 x RJ-45 serial console port
- 1 x USB console port
- 1 x zeroize button

TEMPERATURE

- Operating: -40°C to 50°C (-40°F to 122°F)
- Storage: -40°C to 85°C (-40°F to 185°F)

COMPLIANCE

Designed to meet:

- MIL-STD-810H
- MIL-STD-461G
- FCC Part 15 B
- CE
- RoHS
- REACH

SUPPORTED CISCO IOS XE NETWORK

ESSENTIALS FEATURES

Layer 2:

- IEEE 802.1Q VLAN trunking
- 802.1W Spanning Tree Rapid Reconfiguration

802.1ab Link Layer Discovery Protocol (LLDP)

802.1s - Multiple Spanning Tree Protocol (MSTP) standard compliance

802.1s VLAN Multiple Spanning Trees

802.1Q tunneling

802.3 standard

Unidirectional Link Detection (UDLD)

Cisco Discovery Protocol (CDP)

Unicast MAC filter

VLAN Trunk Protocol (VTP) v2 and v3

EtherChannel

Voice VLAN

Per-VLAN Spanning Tree Plus (PVST+)

Rapid STP (RSTP)

Multicast:

IGMPv1, v2, v3 snooping

IGMP filtering

IGMP querier

Management:

Web UI

MIB

SmartPort

Simple Network Management Protocol (SNMP)

Syslog

Dynamic Host Configuration Protocol (DHCP) server

Switched Port Analyzer (SPAN) session (1)

Full Flexible NetFlow (FnF)

Network Time Protocol (NTP)

Battery backed RTC

Security

Zeroization

Secure boot

Port security

IEEE 802.1X

DHCP snooping

Dynamic Address Resolution Protocol (ARP) inspection

IP Source Guard

Private VLAN

MAC authentication bypass

802.1X multidomain authentication

Storm control - unicast, multicast, broadcast

Secure Copy (SCP)

Secure Shell (SSH)

SNMPv3

TACACS+

RADIUS server/client

MAC address notification

Bridge Protocol Data Unit (BPDU) guard

Quality of Service (QoS)

Ingress policing

Rate limit

Egress queuing/shaping

AutoQoS

Layer 2 IPv6

IPv6 host support

HTTP over IPv6

SNMP over IPv6



EMEA:

Klas,
4th Floor, One Kilmainham Square,
Inchicore Road, Kilmainham,
Dublin 8, Ireland
D08 ETW.

Tel: +353 1 6624270

US

Klas Government
450 Springpark Place,
Suite 1200,
Herndon, VA 20170

Tel: +1 571-375-2500

www.klasgroup.com

KLAS