

VOYAGER/VM

VoyagerVM 3.0 is the latest generation of Voyager compute platform. Based around Intel's Xeon D architecture, it is designed from the outset to provide the maximum performance while operating in temperatures up to 50oC.

VoyagerVM allows applications built for the datacenter to migrate to the edge of the network.

VoyagerVM supports Microsoft Hyper-V and is VMware Ready.



KEY FEATURES

Available with a choice of processors:

- Intel® Pentium® D-1519 4-core
 - 16 GB RAM with option to upgrade to 96 GB
- Intel® Xeon® D-1539 8-core
 - 48 GB RAM with option to upgrade to 96 GB
- Intel® Xeon® D-1559 12-core
 - 48 GB RAM with option to upgrade to 96 GB
- Intel® Xeon® D-1577 16-core
 - 48 GB RAM with option to upgrade to 96 GB
- Two 2.5" SSD slots
- NVMe-based VIK+ with 512 GB storage

- Two 10 Gb SFP+ ports
- Two 1 Gb copper ports
- Rugged enclosure with active air cooling
- Supports Microsoft Hyper-V, Nutanix AHV, VMware ESX/ESXi and KlasOS Keel.
- VMware vSAN and Nutanix AOS certified



SECURE



PORTABLE



RUGGED

EMEA

Klas,
4th Floor, One Kilmainham Square,
Inchicore Road, Kilmainham,
Dublin 8, Ireland
DO8 ETIW.
Tel: +353 1 6624270

US

Klas Government
450 Springpark Place,
Suite 1200,
Herndon, VA 20170
Tel: +1 571-375-2500

www.klasgroup.com

KLAS

VOYAGER/VM

Specifications



PHYSICAL SPECIFICATIONS

- 7.4" W x 6.3" L x 2" H (188 x 160 x 52mm)
- 3.5 lb / 1.6 kg (with no SSDs)

ELECTRICAL SPECIFICATIONS

- 9-36 VDC input
- Power consumption:
 - 4-core (D-1519): 45 W
 - 8-core (D-1539): 55 W
 - 12-core (D-1559): 65 W
 - 16-core (D-1577): 65 W

CONSTRUCTION

- Aluminum chassis with integrated active cooling for increased temperature ranges

OPERATING TEMPERATURE RANGE

- -32 to 50 °C
- 0°C to 50°C for 16-core option

STORAGE TEMPERATURE RANGE

- -40 to 85 °C
- -20°C to 80°C for 16-core option

PORTS

- 2 x 10 Gb SFP+ ports
- 2 x 1 Gb Ethernet ports
- 2 x SATA interfaces
- 2 x USB 3.0 interfaces

- VGA port
- RJ-45 serial console port with hypervisor access
- Removable NVMe Voyager Ignition Key (VIK+) optional removable storage for hypervisor and/or configuration data

CPU OPTIONS

- Intel® Pentium® Processor D-1519 4-Core with 16 GB RAM (order time option of 96 GB RAM)
- Intel® Xeon® Processor D-1539 8-Core with 48 GB RAM (order time option of 96 GB RAM)
- Intel® Xeon® Processor D-1559 12-Core with 48 GB RAM (order time option of 96 GB RAM)
- Intel® Xeon® Processor D-1577 16-Core with 48 GB RAM (order time option of 96 GB RAM)

REMOVABLE STORAGE

- Removable SATA dual SSDs (SSDs not included and are quoted separately)
- Removable NVMe Voyager Ignition Key (VIK+)

SOFTWARE SUPPORT

- KlasOS Keel KVM-based hypervisor
- VMware ESXi 6.x
- Cisco NFVIS with:
 - Cisco KVM-based hypervisor
 - Cisco CSR 1000v
 - Cisco ASA v
- Riverbed Steelhead
- Palo Alto
- Nutanix AHV

MANAGEMENT

- BIOS & hypervisor CLI over console
- IPMI

COMPLIANCE

Compatible with:

- MIL-STD-810
- MIL-STD-461
- FCC Part 15 B
- CE
- RoHS, REACH

